HLL

HORIZONTAL LIFELINE SYSTEM

HORIZONTAL LIFELINE

Horizontal Lifeline System - Rope - Temporary - 2 Person - 100 ft. (30.5 m)

DXFP160020

BENEFITS AND FEATURES

The DEWALT 2-Person Temporary Horizontal Lifeline is lightweight, easy to install and adjustable between 15 ft. (4.6m) and 100 ft. (30.5m). Made of 5/8in. (16mm) kernmantle rope, it includes installation carabiner at each end, tension indicator, two (2) anchor straps and a fall/impact indicator.

DURABILITY: The high strength 5/8 in. (16mm) kern-mantle rope provides excellent wear resistance while the aluminum and stainless steel tensioner provides excellent weather resistance.

COMPACT & LIGHTWEIGHT: Weighing only 18.2 lbs (8.2 Kg.), this temporary horizontal lifeline is easily moved and reused from location to location.

FLEXIBILITY: Can be used for 1 to 2 users and the included web anchor straps allow for use on most vertical beams or posts.



SPECIFICATIONS

Maximum Breaking Strength: 5600 lbs. (25 kN.)

Capacity: 2 Users, 310 lbs. (141 kg) Each

Size: Span length of 15 ft. (4.6 m) to 100 ft. (30.5 m)

Total Weight: 18.2 lbs. (8.26 Kg) Entire System

Material: O-Rings (Forged Alloy Steel)-**Tensioner:** High Strength Alloy Steel-**Lifeline:** 5/8 in. (16 mm.) Kernmantle Rope

RELEVANT STANDARDS

Meets OSHA 1910.66, OSHA 1926.502

WARNINGS

·Read, understand and follow all labels and instructions prior to use.
·Inspect before each use.
·Remove from service if there is evidence of damage or excessive wear.

WARRANTY

2 YEAR LIMITED WARRANTY

2026 DEWALT. DEWALT® and GUARANTEED TOUGH® are registered trademarks of DEWALT Industrial Tool Co. and used under license by DEWALT Fall Protection. All rights reserved. The yellow and black color scheme is a trademark for DEWALT power tool and accessories. A licensee of DEWALT Industrial Tool Co. www.dewalt.com Trademark Licensee: DFP Safety Corp. 20711 Holt Av. Suite 1525 Lakeville, MN 55044 www.dfpsafety.com