ANCHOR

ROOF ANCHOR REUSABLE

ANCHOR POINT

Bolt Down D-Ring - Stainless Steel

DXFP843001

BENEFITS AND FEATURES

The DEWALT stainless steel Bolt Down D-Ring anchor point provides a strong, reusable and corrosion resistant anchor point for multiple applications.



DURABILITY: The stainless steel is highly corrosion and rust resistant.

COMPACT AND LIGHTWEIGHT: At only 0.93 lbs (0.42kg.) this anchor allows for easy installation.

STRENGTH: Meets OSHA and ANSI standards of 5,000 lbs. (23kN) anchor point.

VERSATILITY: Can be used on a wide variety of structural members and fastened with M12 chemical or mechanical fasteners.

SPECIFICATIONS

Length: 4.5 in. (11.4 cm) **Weight:** 0.90 lbs. (404 gr)

Capacity: 310 lbs. (140 Kg)

Breaking Strength: 5,000 lbs. (2267) kg

Materials of construction: Steel

RELEVANT STANDARDS

Meets ANSI Z359.18-2017, OSHA 1926.502, 1910.140

WARNINGS

·Read, understand and follow all labels and instructions prior to use.
·Inspect before each use.
·Remove from service if there is evidence of damage or excessive wear.

WARRANTY

2 YEAR LIMITED WARRANTY

2026 DEWALT. DEWALT® and GUARANTEED TOUGH® are registered trademarks of DEWALT Industrial Tool Co. and used under license by DEWALT Fall Protection. All rights reserved. The yellow and black color scheme is a trademark for DEWALT power tool and accessories. A licensee of DEWALT Industrial Tool Co. www.dewalt.com Trademark Licensee: DFP Safety Corp. 20711 Holt Av. Suite 1525 Lakeville, MN 55044 www.dfpsafety.com