WINCH

CONFINED SPACE

WINCH

100 ft. (30.4 m)

DXFP474000-100



BENEFITS AND FEATURES

The DEWALT 100 ft. (30.4m) Galvanized cable Personnel bi-directional winch for confined spaces. Equipped with the Mounting plate and hardware for mounting to DEWALT Tripod and Davits. Also, is equipped with a secondary brake mechanism which arrest the fall and reduces the dynamic load impact felt on the user in the event of a fall, to less than 28 lbs. (12.7 kg).

FLEXIBILITY: With a gear ratio of 6 : 1, the DEWALT Winch provides the ability to easily rescue or retrieve personnel in confined space applications.

COMPACT AND LIGHTWEIGHT: Weighing only 41.6 lbs. (18.8 kg.) the DEWALT Winch allows users to work with more freedom of motion and provides rescue/retrieval option.

SPECIFICATIONS

Maximum Breaking Strength: 5,000 lbs. (23 kN)

Fall Arrest Capacity: 310 lbs. (141 kg) OSHA 420 lbs. (190 kg) 1 user.

Rescue Capacity: 420 lbs. (191 kg) 1 users.

Max Lenght: 100 ft. (30.4 m) **Weight:** 40.8 lbs. (18.5 kg)

Material: (Casing) High Strength Alloy Steel
(Lifeline) Galvanized Steel Cable 1/4 in. (6 mm)

Connector Winch: 3600 lbs. (16kN) Gate Steel Snap Hook

RELEVANT STANDARDS

Meets ANSI Z359.4-2013

WARNINGS

·Read, understand and follow all labels and instructions prior to use.
·Inspect before each use.
·Remove from service if there is evidence of damage or excessive wear.

WARRANTY

2 YEAR LIMITED WARRANTY