VLL

VERTICAL LIFELINE SYSTEM

VERTICAL LIFELINE

Polydac Rope - Snap Hook With Taped End - 50 ft. (15 m)

DXFP101050

BENEFITS AND FEATURES

The DEWALT 50 ft. (15 m) Polydac Vertical Rope Lifeline has a diameter of 5/8 in. (16 mm) with a Locking Snap hook on the anchor end with the other end being cut and taped.



ABRASION RESISTANT: Polydac rope resists abrasion and water for extended use.

STRENGTH & DURABILITY: Alloy steel snap hook with zinc plating for high strength and long life.

STRENGTH: Meets OSHA and ANSI standards for 3,600 lb. (16kN) gate. Minimum breaking strength 5,000 lbs (23kN).

SPECIFICATIONS

Maximum Breaking Strength: 5,000 lbs. (23 kN.)

Capacity: 310 lbs. (141 kg)

Size: 5/8 in. (16 mm) Thick, 50 ft (15 m) Long

Weight: 7.8 lbs. (3.54 Kg)

Material: Galvanized Alloy Steel Snap Hook with Silver or Golden passivation, High strength Polydac Twisted Rope

RELEVANT STANDARDS

Meets ANSI Z359.1-2007, OSHA 1910.66, OSHA 1926.502

WARNINGS

·Read, understand and follow all labels and instructions prior to use.
·Inspect before each use.
·Remove from service if there is evidence of damage or excessive wear.

WARRANTY

2 YEAR LIMITED WARRANTY

2026 DEWALT. DEWALT® and GUARANTEED TOUGH® are registered trademarks of DEWALT Industrial Tool Co. and used under license by DEWALT Fall Protection. All rights reserved. The yellow and black color scheme is a trademark for DEWALT power tool and accessories. A licensee of DEWALT Industrial Tool Co. www.dewalt.com Trademark Licensee: DFP Safety Corp. 20711 Holt Av. Suite 1525 Lakeville, MN 55044 www.dfpsafety.com