ANCHOR

BEEM ANCHOR

BEAM ANCHOR

Movable Trolley - Fits 3.1 in. (8.0 cm.) To 9.8 in. (25 cm.) Flange

DXFP846101

BENEFITS AND FEATURES

The DEWALT Beam Trolley Anchor is capable of being installed on the flange of horizontal beams. The variable position jaw adjustment enables it to be installed on flange widths of 3.1 in. (8.0 cm) to 9.8 in. (25 cm) and the high impact rollers provide easy mobility horizontally along a beam.

DURABILITY: The aluminum alloy and stainless steel construction of the beam trolley provides exceptional strength for a long lasting, movable anchor point.



COMPACT AND LIGHTWEIGHT: Weighing only 8.6 lbs. (3.9 Kg), this beam anchor is easily moved and reused from location to location.

FLEXIBILITY: Can be used as a temporary horizontal anchor point on steel beam flanges. High impact rollers provide complete motion along horizontal beams.

STRENGTH: Meets OSHA and ANSI standards of 5,000 lbs. (23 kN) anchor point.

SPECIFICATIONS

Length: 18 in. (45.4 cm) **Width :** 5.94 in. (15.1cm.) **Height:** 6.73 in. (17.1 cm)

Capacity: 310 lbs. (140 Kg.)

Breaking Strength: 5,000 lbs. (23 kN)

Materials of construction: Aluminum Alloy, Steinless Steel

RELEVANT STANDARDS

Meets ANSI Z359.18-2017 Type A, OSHA 1926.502, 1910.140

WARNINGS

·Read, understand and follow all labels and instructions prior to use.
·Inspect before each use.
·Remove from service if there is evidence of damage or excessive wear.

WARRANTY

2 YEAR LIMITED WARRANTY

2026 DEWALT. DEWALT® and GUARANTEED TOUGH® are registered trademarks of DEWALT Industrial Tool Co. and used under license by DEWALT Fall Protection. All rights reserved. The yellow and black color scheme is a trademark for DEWALT power tool and accessories. A licensee of DEWALT Industrial Tool Co. www.dewalt.com Trademark Licensee: DFP Safety Corp. 20711 Holt Av. Suite 1525 Lakeville, MN 55044 www.dfpsafety.com