ANCHOR STRAP

CONCRETE ANCHOR

4 ft. (1.2 m) CONCRETE ANCHOR STRAP

Web Loop On Both Ends

DXFP813004

BENEFITS AND FEATURES

The DEWALT 4 ft.(1.2 m) concrete web anchor strap with web loop provides a strong, durable and flexible temporary fall protection anchor point. It is designed to be choked to rebar and embedded into the poured concrete and cut off once construction is completed.



DURABILITY: The 1-3/4 in. (4.4 cm) polyester webbing strength member with the 2 in. (5.08 cm) polyester webbing wear pad provides exceptional strength, wear, oil, dust and water protection.

ECONOMICAL: Provides an economical means to ensure sufficient anchor points are in place throughout the construction process.

STRENGTH: Meets OSHA and ANSI standards of 5,000 lbs. (23kN) anchor point.

FLEXIBILITY: Provides an economical means to ensure sufficient anchor points are in place throughout the construction process.

SPECIFICATIONS

Length: 4 ft. (1.2 m)

Capacity: 310 lbs. (140) Kg

Breaking Strength: 5,000 lbs. (2267) kg

Materials of construction: Polyester, Steel

RELEVANT STANDARDS

Meets ANSI Z359.18-2017 Type T, OSHA 1926.502, 1910.140

WARNINGS

·Read, understand and follow all labels and instructions prior to use.
·Inspect before each use.
·Remove from service if there is evidence of damage or excessive wear.

WARRANTY

2 YEAR LIMITED WARRANTY

2026 DEWALT. DEWALT® and GUARANTEED TOUGH® are registered trademarks of DEWALT Industrial Tool Co. and used under license by DEWALT Fall Protection. All rights reserved. The yellow and black color scheme is a trademark for DEWALT power tool and accessories. A licensee of DEWALT Industrial Tool Co. www.dewalt.com Trademark Licensee: DFP Safety Corp. 20711 Holt Av. Suite 1525 Lakeville, MN 55044 www.dfpsafety.com