ANCHOR

CONCRETE ANCHOR

ANCHOR POINT

Single Point Anchor Swivel for Concrete Structure

DXFP843101

BENEFITS AND FEATURES

The DEWALT Swiveling Anchor Point for Concrete provides a strong, reusable and corrosion resistant anchor point for post-construction concrete applications.

DURABILITY: Galvanized Zinc with Silver/Yellow passivation high alloy steel is highly corrosion and rust resistant.

COMPACT AND LIGHTWEIGHT: At only 2.02 lbs. (0.91 kg) this anchor allows for easy installation.

STRENGTH: Meets OSHA and ANSI standards of 10,000 lbs. (45 kN) anchor point.

VERSATILITY: Compatible with 5/8 in. (1.58 cm) concrete fastener to be installed in concrete block of minimum 5 in.(12.7 cm) thickness into a predrilled hole of 3/4 In. (1.9 cm) in diameter up to 4.5 in. (11.4 cm) depth.



SPECIFICATIONS

Length: 4.45 in. (11.3 cm) **Width:** 3 in. (7.62 cm)

Capacity: 310 lbs. (140 Kg)

Breaking Strength: 10,000 lbs. (45 kN)

Materials of construction: High Stregth Alloy Steel

RELEVANT STANDARDS

Meets ANSI Z359.18-2017 Type A, OSHA 1926.502, 1910.140

WARNINGS

·Read, understand and follow all labels and instructions prior to use.
·Inspect before each use.
·Remove from service if there is evidence of damage or excessive wear.

WARRANTY

2 YEAR LIMITED WARRANTY

2026 DEWALT. DEWALT® and GUARANTEED TOUGH® are registered trademarks of DEWALT Industrial Tool Co. and used under license by DEWALT Fall Protection. All rights reserved. The yellow and black color scheme is a trademark for DEWALT power tool and accessories. A licensee of DEWALT Industrial Tool Co. www.dewalt.com Trademark Licensee: DFP Safety Corp. 20711 Holt Av. Suite 1525 Lakeville, MN 55044 www.dfpsafety.com