ANCHOR

ROOF ANCHOR SINGLE USE

ROOF ANCHOR

Single Use - Zinc Coated Steel

DXFP841002

BENEFITS AND FEATURES

The DEWALT Single Use Roof Anchor is designed for use on the slope of pitched roofs. The anchor is made of coated steel with a 1 in. (2.54 cm) hole in diameter connection point.

DURABILITY: The one-piece design and zinc plated galvanized steel provides a long lasting temporary anchor point.

COMPACT AND LIGHTWEIGHT: At only 0.93 lbs (0.42 kg) this anchor allows for easy installation.



STRENGTH: Meets OSHA and ANSI standards of 5,000 lbs. (23kN) anchor point.

ECONOMICAL: Provides an economical means to ensure su icient anchor points are in place throughout the construction process.

SPECIFICATIONS

Overall Length: 13.1 in. (33.2 cm.) **Width:** 2.23 in. (5.68 cm)

Capacity: 310 lbs. (140 Kg.)

Breaking Strength: 5,000 lbs. (2267) kg

Materials of construction: Steel

RELEVANT STANDARDS

Meets ANSI Z359.18-2017 Type A, OSHA 1926.502, 1910.140

WARNINGS

·Read, understand and follow all labels and instructions prior to use.
·Inspect before each use.
·Remove from service if there is evidence of damage or excessive wear.

WARRANTY

2 YEAR LIMITED WARRANTY

2026 DEWALT. DEWALT® and GUARANTEED TOUGH® are registered trademarks of DEWALT Industrial Tool Co. and used under license by DEWALT Fall Protection. All rights reserved. The yellow and black color scheme is a trademark for DEWALT power tool and accessories. A licensee of DEWALT Industrial Tool Co. www.dewalt.com Trademark Licensee: DFP Safety Corp. 20711 Holt Av. Suite 1525 Lakeville, MN 55044 www.dfpsafety.com