ANCHOR

ROOF ANCHOR PERMANENT USE

ROOF ANCHOR

Permanent Use - Stainless Steel

DXFP842002

BENEFITS AND FEATURES

The DEWALT Stainless Steel Roof Anchor with D-Rings for Permanent Use, is an ideal permanent Anchorage device to be fixed on structural members used in roofing.

DURABILITY: The one-piece design and stainless steel material, provides a long lasting permanent anchor point. D-Rings on each end.



COMPACT AND LIGHTWEIGHT: At only 0.83 lbs. (3.76 gr) this anchor allows for easy installation.

STRENGTH: Meets OSHA and ANSI standards of 5,000 lbs. (23kN) anchor point.

ECONOMICAL: Provides an economical means to ensure sufficient anchor points are in place throughout the construction process.

SPECIFICATIONS

Overall Length: 18.1 in. (46.1 cm) **Width:** 1.73 in. (4.40 cm)

Capacity: 310 lbs. (140 Kg)

Breaking Strength: 5,000 lbs. (23 kN)

Materials: Base Plate : Stainless Steel, D-Ring : Medium carbon Steel

RELEVANT STANDARDS

Meets ANSI Z359.18-2017, OSHA 1926.502, 1910.140

WARNINGS

·Read, understand and follow all labels and instructions prior to use.
·Inspect before each use.
·Remove from service if there is evidence of damage or excessive wear.

WARRANTY

2 YEAR LIMITED WARRANTY

2026 DEWALT. DEWALT® and GUARANTEED TOUGH® are registered trademarks of DEWALT Industrial Tool Co. and used under license by DEWALT Fall Protection. All rights reserved. The yellow and black color scheme is a trademark for DEWALT power tool and accessories. A licensee of DEWALT Industrial Tool Co. www.dewalt.com Trademark Licensee: DFP Safety Corp. 20711 Holt Av. Suite 1525 Lakeville, MN 55044 www.dfpsafety.com