DEWALT
DROP PREVENTION

TOOL ATTACHMENTS

ELASTIC TOOL ATTACHMENT 5 LB.

ELASTIC TOOL ATTACHMENT 5 LB.

DXDP710500



BENEFITS AND FEATURES

The DEWALT Elastic Tool Attachment is designed to be used with the DEWALT Quick Connect Tool Attachment DXDP710211, and together they allow for quick exchanges of multiple tools weighing 5 lbs. (2.3 Kg) or less. Once connected, it becomes a key component to a tethering system intended to prevent accidental drops that can lead to injuries and property damage.

SECURITY: Captive eye, dual-action, locking carabiner for worry free operation

FLEXIBILITY: Elastic, bungee style webbing provides a wide working range

LIGHTWEIGHT: Aluminum carabiner provides less weight that steel connections

SPECIFICATIONS

Relaxed length: 28 in. (71 cm)

Extended length: 43 in. (109 cm)

Maximum safe working capacity: 5 lbs (2.3 kg)

Materials of construction: Polyester and aluminum

RELEVANT STANDARDS

Meets ANSI/ISEA 121-2023 standard

WARNINGS

·Read, understand and follow all labels and instructions prior to use.
·Inspect before each use.
·Remove from service if there is evidence of damage or excessive wear.

WARRANTY

2 YEAR LIMITED WARRANTY

2026 DEWALT. DEWALT® and GUARANTEED TOUGH® are registered trademarks of DEWALT Industrial Tool Co. and used under license by DEWALT Fall Protection. All rights reserved. The yellow and black color scheme is a trademark for DEWALT power tool and accessories. A licensee of DEWALT Industrial Tool Co. www.dewalt.com Trademark Licensee: DFP Safety Corp. 20711 Holt Av. Suite 1525 Lakeville, MN 55044 www.dfpsafety.com