DEWALT FALL PROTECTION

ANCHOR

DROP THROUGH ANCHOR

DROP THROUGH ANCHOR with 6 ft. [1.8 m] CABLE

6 in. (15.2 cm) Plate

DXFP822001

BENEFITS AND FEATURES

The DEWALT 6 ft. (1.8m) Reusable Drop Through Swiveling Cable Anchor is designed to be used in either steel or concrete to provide an overhead fall protection anchor point.

DURABILITY: The 1/4 in. (6 mm) galvanized cable provides exceptional strength and wear resistance.

COMPACT AND LIGHTWEIGHT: Weighing only 2.4 lbs. (1.09 kg), this temporary anchor is easily moved and reused from location to location.



STRENGTH: Meets OSHA and ANSI standards of 5,000 lbs. (23kN) anchor point.

FLEXIBILITY: Can be used as a vertical or horizontal temporary anchor point around beams, posts or other structural members.

SPECIFICATIONS

Length: 6 ft. (1.8 m)

Breaking Strength: 5,000 lbs. (2267 kg)

Materials of construction: Galvanized Cable, Polished Steel

RELEVANT STANDARDS

Meets ANSI Z359.18-2017 Type A, OSHA 1926.502, 1910.140

WARNINGS

·Read, understand and follow all labels and instructions prior to use.
·Inspect before each use.
·Remove from service if there is evidence of damage or excessive wear.

WARRANTY

2 YEAR LIMITED WARRANTY

2026 DEWALT. DEWALT® and GUARANTEED TOUGH® are registered trademarks of DEWALT Industrial Tool Co. and used under license by DEWALT Fall Protection. All rights reserved. The yellow and black color scheme is a trademark for DEWALT power tool and accessories. A licensee of DEWALT Industrial Tool Co. www.dewalt.com Trademark Licensee: DFP Safety Corp. 20711 Holt Av. Suite 1525 Lakeville, MN 55044 www.dfpsafety.com