DEWALT
DROP PREVENTION

TOOL HOLDERS

TAPE MEASURE HOLDER

TAPE MEASURE HOLDER

DXDP610200



BENEFITS AND FEATURES

The DEWALT Tape measure holder adjusts to fit most tape measures up to 35 Ft. (10.67 M.). The steel D-ring allows the quick connection of a tool lanyard to the holder to protect workers and property below from damage. The stainless clip allows the holder to be easily attached to harnesses and work belts.

VERSATILITY: Hook and loop closures allow for the fit of most tape measures up to 35 feet (10.67 meters)

SECURE CONNECTION: Hook and loop closures and elastic straps allow for secure and safe fit.

DURABILITY: Rugged polyester material and steel d-ring for durability and longer life.

SPECIFICATIONS

Dimensions: H 5.11 W 3.74 in. (13 x 95 cm)

Net Weight in lbs (Product): 0.286 (0.13 Kg)

Maximum safe working capacity: 2 lbs (0.9 kg)

Materials of construction: Polyester and steel

RELEVANT STANDARDS

Meets ANSI/ISEA 121-2018 standard

WARNINGS

·Read, understand and follow all labels and instructions prior to use.
·Inspect before each use.
·Remove from service if there is evidence of damage or excessive wear.

WARRANTY

2 YEAR LIMITED WARRANTY

2026 DEWALT. DEWALT® and GUARANTEED TOUGH® are registered trademarks of DEWALT Industrial Tool Co. and used under license by DEWALT Fall Protection. All rights reserved. The yellow and black color scheme is a trademark for DEWALT power tool and accessories. A licensee of DEWALT Industrial Tool Co. www.dewalt.com Trademark Licensee: DFP Safety Corp. 20711 Holt Av. Suite 1525 Lakeville, MN 55044 www.dfpsafety.com

DEWALT
DROP PREVENTION

TOOL LANYARDS

COILED TOOL LANYARD

COILED TOOL LANYARD

DXDP710900



BENEFITS AND FEATURES

The DEWALT Coiled Tool Lanyard with dual swiveling carabiners is designed for use with small hand tools and other PPE weighing up to 2 lbs (0.9kg). The coiled design reduces lanyard length to prevent snags and tangles. Once connected, it becomes a key component to a tethering system intended to prevent accidental drops that can lead to injuries and property damage.

DURABILITY: Polyurethane coated steel cable provides corrosion resistance and improved life.

SECURE CONNECTION: Screw-lock, dual-action carabiner provides a sure connection

TANGLE FREE: Coiled design with swivel end for tangle free operation

SPECIFICATIONS

Relaxed length: 4 in. (10 cm)

Extended length: 60 in. (152 cm)

Maximum safe working capacity: 2 lbs (0.9 kg)

Materials of construction: PU and Stainless steel

RELEVANT STANDARDS

Meets ANSI/ISEA 121-2023 standard

WARNINGS

·Read, understand and follow all labels and instructions prior to use.
·Inspect before each use.
·Remove from service if there is evidence of damage or excessive wear.

WARRANTY

2 YEAR LIMITED WARRANTY

2026 DEWALT. DEWALT® and GUARANTEED TOUGH® are registered trademarks of DEWALT Industrial Tool Co. and used under license by DEWALT Fall Protection. All rights reserved. The yellow and black color scheme is a trademark for DEWALT power tool and accessories. A licensee of DEWALT Industrial Tool Co. www.dewalt.com Trademark Licensee: DFP Safety Corp. 20711 Holt Av. Suite 1525 Lakeville, MN 55044 www.dfpsafety.com