DL 60 HLS

CONFINED SPACE

HORIZONTAL LIFELINE SYSTEM

60 ft. (18.2 m)

DXFP160060



High-speed and fine-tuning retraction handle

BENEFITS AND FEATURES

The DEWALT® DL60, Retractable Horizontal Lifeline with adjustable span length up to 60 ft. (18.2 m), is a self-contained, retractable temporary horizontal lifeline system that is quick and easy to set up and tear down.

CONVENIENCY: High-speed and fine-tuning retraction handles for quick and easy installation and removal. (Other side)

DURABILITY: High Impact Strength Polymer casing, reinforced corners to ensure structural integrity.

TENSION INDICATOR:
Gives a visible conformation that the lifeline tension is set to the proper tension.



SPECIFICATIONS

Maximum Breaking Strength: 5,000 lbs. (23 kN)

Load Capacity: 310 lbs. (141 kg) each User O-Ring (2 users)

Max Lenght: 60 ft. (18.2 m) **Unit Weight:** 31.7 lbs. (14.5 kg)

Connector SRL: 3600 lbs. (16kN) Gate Steel Carabiner

Material: (Casing) High Impact Strength Polymer
(Lifeline) Galvanized Steel Cable 1/4 in. (6.4 mm)

RELEVANT STANDARDS

OSHA 1926.502 and 1910.140

EN 795:2012, Type C
CEN/TS 16415:2013, Type C (for up to 2 users)

WARNINGS

·Read, understand and follow all labels and instructions prior to use.
·Inspect before each use.
·Remove from service if there is evidence of damage or excessive wear.

WARRANTY

2 YEAR LIMITED WARRANTY

2026 DEWALT. DEWALT® and GUARANTEED TOUGH® are registered trademarks of DEWALT Industrial Tool Co. and used under license by DEWALT Fall Protection. All rights reserved. The yellow and black color scheme is a trademark for DEWALT power tool and accessories. A licensee of DEWALT Industrial Tool Co. www.dewalt.com Trademark Licensee: DFP Safety Corp. 20711 Holt Av. Suite 1525 Lakeville, MN 55044 www.dfpsafety.com