ANCHOR

ANCHOR POINT REUSABLE

ANCHOR POINT

Reusable - Steel Girder

DXFP845001

BENEFITS AND FEATURES

The DEWALT Steel Girder Anchor is a removable and reusable anchor point to be mounted on solid steel structures, girders and steel I-beams. It can be installed very easily with one hand and is extremely portable. The maximum thickness of the structure on which installation is possible is 1.57 in. (4 cm).

DURABILITY: The combination of galvanized and stainless steel provides exceptional strength, wear and corrosion resistance..

COMPACT AND LIGHTWEIGHT: Weighing only 1.2 lbs. (0.54 kg), this temporary anchor is easily moved and reused from location to location with one hand.

STRENGTH: Meets OSHA and ANSI standards of 5,000 lbs. (23 kN) anchor point.

VERSATILITY: Can be used as a vertical or horizontal temporary anchor point on steel structural members. Hole width of 13/16 in. (2.1cm) to 1-3/16 in. (3 cm). Material thickness up to 1-9/16 in. (4 cm).



SPECIFICATIONS

Length: 4.7 in. (1.4 cm) **Weight:** 1.21 lbs. (0.55 kg)

Capacity: 310 lbs. (140 Kg)

Breaking Strength: 5,000 lbs. (2267) kg.

Materials of construction: Alloy Steel, S. Steel Moulded Polymer

RELEVANT STANDARDS

Meets ANSI Z359.18-2017 Type A, OSHA 1926.502, 1910.140

WARNINGS

·Read, understand and follow all labels and instructions prior to use.
·Inspect before each use.
·Remove from service if there is evidence of damage or excessive wear.

WARRANTY

2 YEAR LIMITED WARRANTY

2026 DEWALT. DEWALT® and GUARANTEED TOUGH® are registered trademarks of DEWALT Industrial Tool Co. and used under license by DEWALT Fall Protection. All rights reserved. The yellow and black color scheme is a trademark for DEWALT power tool and accessories. A licensee of DEWALT Industrial Tool Co. www.dewalt.com Trademark Licensee: DFP Safety Corp. 20711 Holt Av. Suite 1525 Lakeville, MN 55044 www.dfpsafety.com