VLL

VERTICAL LIFELINE SYSTEM

VERTICAL LIFELINE

Polysteel Rope - Snap Hook With Taped End - 25 ft. (7.6 m)

DXFP100025

BENEFITS AND FEATURES

The DEWALT 25 ft. (7.6 m) Polysteel Vertical Rope Lifeline has a diameter of 5/8 in. (16 mm) with a Locking Snap hook on the anchor end with the other end being cut and taped.



ABRASION RESISTANT: Polysteel rope resists abrasion and water for extended use.

STRENGTH & DURABILITY: Alloy steel snap hook with zinc plating for high strength and long life.

STRENGTH: Meets OSHA and ANSI standards for 3,600 lbs. (16kN) gate.
Minimum breaking strength 5,000 lbs. (23kN).

SPECIFICATIONS

Maximum Breaking Strength: 5,000 lbs. (23 kN.)

Capacity: 310 lbs. (141 kg)

Size: 5/8 in. (16 mm.) Thick, 25 ft (7.6 m) Long

Weight: 4.23 lbs. (1.92 Kg)

Material: Galvanized Alloy Steel Snap Hook with Silver or Golden passivation, High strength Polysteel Twisted Rope

RELEVANT STANDARDS

Meets ANSI Z359.1-2007, OSHA 1910.66, OSHA 1926.502

CAN/CSA Z259. 2.5-17 (R2021)

WARNINGS

·Read, understand and follow all labels and instructions prior to use.
·Inspect before each use.
·Remove from service if there is evidence of damage or excessive wear.

WARRANTY

2 YEAR LIMITED WARRANTY

2026 DEWALT. DEWALT® and GUARANTEED TOUGH® are registered trademarks of DEWALT Industrial Tool Co. and used under license by DEWALT Fall Protection. All rights reserved. The yellow and black color scheme is a trademark for DEWALT power tool and accessories. A licensee of DEWALT Industrial Tool Co. www.dewalt.com Trademark Licensee: DFP Safety Corp. 20711 Holt Av. Suite 1525 Lakeville, MN 55044 www.dfpsafety.com