DAVIT SYSTEM

CONFINED SPACE

DAVIT SYSTEM

5 Piece Davit System, 36 in. (0.91 m) Mast with 60 ft. (18.2 m) Winch and 60 ft. (18.2 m) Retrieval SRL

DXFP451919-036

BENEFITS AND FEATURES

The DEWALT 5 Piece Davit System with 36 in. (0.91 m) mast, with a 60 ft. (18.2 m) Winch and 60 ft. (18.2 m) Retrieval SRL, provides a portable Fall Protection and Access system for vertical entry/egress into confined spaces.

DURABILITY: Built with high strength aluminum alloy, the DEWALT Davit System components are designed to ensure longevity, even in the toughest conditions.

FLEXIBILITY: Ahe DEWALT Davit System breaks down into five components for easy storage, transport and setup. No tools are required for assembly Includes pre-installed Winch and Retrieval SRL Mounting brackets Removable legs for easy transportation and installation purpose Multiple anchorage points for fall protection and rescue applications Built-in swivel feature allows the davit column assembly to be rotated up to 360°.



SPECIFICATIONS

Maximum Breaking Strength: 5,000 lbs. (23 kN)

Capacity: 310 lbs. (141 kg) OSHA 620 lbs. (282 kg) for Rescue

Max Height: 72 in. (1.8 m)

Weight: 263.4 lbs. 119.4 kg)

Working Width: 43 in. (1.1 m) to 59 in. (1.5 m)

Material: High Strength Aluminum Alloy

ADJUSTABILITY: Davit System Boom comes with 3 adjustment positions for the user to adjust the height to meet various situations: Min. Height: 47 in. (1.2 m) with 36 in. (0.91 m) offset
Middle Height: 61 in. (1.5 m) with 33 in. (0.84 m) offset
Max. Height: 72 in. (1.8 m) with 26 in. (0.66 m) offset.

RELEVANT STANDARDS

Meets ANSI Z359.18-2017 Type A - OSHA 1926.502 and 1910.66

WARNINGS

·Read, understand and follow all labels and instructions prior to use.
·Inspect before each use.
·Remove from service if there is evidence of damage or excessive wear.

WARRANTY

2 YEAR LIMITED WARRANTY