VLL

ROPE GRAB ASSEMBLY

VERTICAL LIFELINE

Rope Grab - Removable - Manual - 1.5 ft. (0.4 m) Energy Absorbing Lanyard - 5/8 in. (16 mm) Rope

DXFP150010

BENEFITS AND FEATURES

The DEWALT removable rope grab with energy absorbing lanyard moves along the lifeline with the user either up or down. It is removable and has a unique anti-panic feature and a factory attached energy absorber with steel snap hook.

DURABILITY: The galvanized high strength alloy steel rope grab and snap hook will resist rust and corrosion for extended life.

FLEXIBILITY: The removable design allows you to place it in various vertical lifelines from 1/2 in. (12 mm) to 5/8 in. (16 mm) thick.

SAFETY: The unique anti-panic feature ensure no accidental disengagement and the intregal energy absorbing lanyard reduces forces in the event of a fall.



SPECIFICATIONS

Rope Grab Maximum Breaking Strength: 3372 lbs. (15 kN.)

Energy Absorbing Lanyard: 6000 lbs. (26 kN.)

Capacity: 310 lbs. (141 kg)

Size: 3.07 in. (78 mm) Tall, 1.85 in. (47mm) Deep not including the 1.97 in. (50 mm) connecting eye - **Weight:** 2.82 lbs. (1.28 Kg.

Material: Galvanized Alloy Steel Snap Hook with Silver or Golden passivation, Webbing 1.75 in.(44 mm) wide, high tenacity polyester

RELEVANT STANDARDS

Meets ANSI Z359.15-2014, OSHA 1910.66, OSHA 1926.502

WARNINGS

·Read, understand and follow all labels and instructions prior to use.
·Inspect before each use.
·Remove from service if there is evidence of damage or excessive wear.

WARRANTY

2 YEAR LIMITED WARRANTY

2026 DEWALT. DEWALT® and GUARANTEED TOUGH® are registered trademarks of DEWALT Industrial Tool Co. and used under license by DEWALT Fall Protection. All rights reserved. The yellow and black color scheme is a trademark for DEWALT power tool and accessories. A licensee of DEWALT Industrial Tool Co. www.dewalt.com Trademark Licensee: DFP Safety Corp. 20711 Holt Av. Suite 1525 Lakeville, MN 55044 www.dfpsafety.com