I BEAM ANCHOR

CONFINED SPACE

# I BEAM STANCHION ANCHOR

## DXFP160001



## BENEFITS AND FEATURES

The DEWALT® I BEAM STANCHION ANCHOR: A portable and extremely easy to install Anchor Post for Horizontal Line on Steel construction I-Beam sections.

**FLEXIBILITY:** Compatible with I-Beam having flange width of 5.9 in. (15.0 cm) to 8.7 in. (22.0 cm)

**DURABILITY:** The DEWALT rugged strength alloy steel ensures longevity, even in the toughest conditions.

**STRENGTH:** Meets OSHA and ANSI standards for 5,000 lbs. (23 kN).

## SPECIFICATIONS

**Maximum Breaking Strength:** 5,000 lbs. (23 kN)

**Capacity:** 310 lbs. (141 kg) each user - (Total of 2 user)

**Height :** 28.7 in. (73 cm) **Width:** 8.4 in. (21 cm)

**Weight:** 28 lbs. (13 kg)

**Material:** High Strength Alloy Steel

## RELEVANT STANDARDS

**ANSI Z359.18-2017 Type D - OSHA 1926.502 and 1910.140**

## WARNINGS

·Read, understand and follow all labels and instructions prior to use.
·Inspect before each use.
·Remove from service if there is evidence of damage or excessive wear.

## WARRANTY

**2 YEAR LIMITED WARRANTY**

2026 DEWALT. DEWALT® and GUARANTEED TOUGH® are registered trademarks of DEWALT Industrial Tool Co. and used under license by DEWALT Fall Protection. All rights reserved. The yellow and black color scheme is a trademark for DEWALT power tool and accessories. A licensee of DEWALT Industrial Tool Co. www.dewalt.com Trademark Licensee: DFP Safety Corp. 20711 Holt Av. Suite 1525 Lakeville, MN 55044 www.dfpsafety.com