FALL PROTECTION

VLL WITH ROPE ADJUSTOR

VERTICAL LIFELINE WITH ROPE ADJUSTOR

Integral 2 ft. (0.6 m) Energy Absorber Lanyard

DXFP210050



BENEFITS AND FEATURES

The DEWALT® 50 ft. (15.2 m) Vertical Lifeline with Rope Adjustor is designed as a key component for roof-top safety. The rope is water and abrasion resistant for strength and durability, while the built-in rope adjustor provides the versatility of free movement or fixing in place for fall restraint. When used with a DEWALT® rooftop anchor and harness it becomes and integral piece in a personal fall arrest system.

ABRASION RESISTANT: Poly Steel rope resists abrasion and water for longer life.

STRENGHT & DURABILITY: Alloy steel hardware with silver plating for high strength and long life.

EASY OF MOVEMENT: Manual positioning device allows for smooth movement around working surface.

SPECIFICATIONS

Total Length: 50 ft. (15.2 m)
Worker Capacity Range: 130-310 lbs. (58-140 kg)
Minimum Breaking Strength: 5,000 lbs. / 2267 kg Min. Static Strength
Material of Construction: Poly Steel Rope, Alloy Steel, Polyester
Weight: 8.2 lbs. / 3.7 kg
Meets: ANSI Z359.1-2007, OSHA 1910.140, OSHA 1926.502
CAN/CSA-Z259.2.5-17 (R2021)

WARNINGS

·Read, understand and follow all labels and instructions prior to use.
·Inspect before each use.
·Remove from service if there is evidence of damage or excessive wear.

WARRANTY

2 YEAR LIMITED WARRANTY

2026 DEWALT. DEWALT® and GUARANTEED TOUGH® are registered trademarks of DEWALT Industrial Tool Co. and used under license by DEWALT Fall Protection. All rights reserved. The yellow and black color scheme is a trademark for DEWALT power tool and accessories. A licensee of DEWALT Industrial Tool Co. www.dewalt.com Trademark Licensee: DFP Safety Corp. 20711 Holt Av. Suite 1525 Lakeville, MN 55044 www.dfpsafety.com