TRIPOD SYSTEMS

7 ft. (2.10m) Tripod with 60 ft. (18.2 m) Retrieval SRL

DXFP421400-007

BENEFITS AND FEATURES

The DEWALT 7 ft. (2.13 m) Adjustable Tripod with bag and DEWALT 60 ft. (18.2 m) Retrieval SRL provides a portable Fall Protection and Access system for vertical entry/egress into confined spaces. Weighing only 87.6 lbs. (39.7 kg) the DEWALT 7 ft. (2.13 m) Adjustable legs for easy transportation and installation purposes anchor point for fall protection and rescue applications.

FLEXIBILITY: Adjustable Tripod folds down to 63 in. (1.6 m) length for easy storage and transport. No tools are required for assembly
Dual pulleys built into the tripod head for winch/SRL lifeline.
Includes 1 pre-installed Winch or Retrieval SRL Mounting bracket.

DURABILITY: Built with high strength aluminum alloy, the DEWALT Tripod System components are designed to ensure longevity, even in the toughest conditions.



60 ft. (18.2 m) Retrieval SRL

SPECIFICATIONS

Maximum Breaking Strength: 5,000 lbs. (23 kN)

Fall Arrest Capacity: 310 lbs. (141 kg) OSHA 420 lbs. (190 kg) 1 user.

Rescue Capacity: 620 lbs. (280 kg) 2 users.

Min Height: 48 in.(1.2 m) with 25 in. (0.6 m) hole clearance

Max Height: 89 in. (2.2 m) with 46 in. (1.1 m) hole clearance

Material: (Head) Prime quality aluminum alloy. ED Coated black (Finish)
(Locking Pins) Prime quality aluminum alloy eye bolt & stainless steel. Deburred & Polished (Finish)
(Legs) Prime quality aluminum alloy. Anodized (Finish)

RELEVANT STANDARDS

Tripod: ANSI Z359.18-2017 Type A - Retrieval SRL: ANSI Z359.14 - 2021 - OSHA 1926.502 and 1910.66

WARNINGS

·Read, understand and follow all labels and instructions prior to use.
·Inspect before each use.
·Remove from service if there is evidence of damage or excessive wear.

WARRANTY

2 YEAR LIMITED WARRANTY